



## **Declaration of Performances (DoP)**

No. 20170056

**Product Type** 

PT1TY2 LSOH OSCR / RE-2X(ST)HSWAH (300/500 V)

\* 1 PR to 20PR - 0,5 mm<sup>2</sup>

\* 1 PR to 20PR - 0,75 mm<sup>2</sup>

\* 1 PR to 20PR - 1,00 mm<sup>2</sup>

\* 1 PR to 20PR - 1,5 mm<sup>2</sup>

\* 1 PR to 10PR - 2,5 mm<sup>2</sup>

**Batch or Serial Number** 

M3 2 XXX XXYYYZZZ

Intended use:

Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke

## System 1+

of assessment and verification of constancy of performance

## Approved laboratory body No. NB 2661

The performance of the product identified above is in conformity with the declared performance(s) This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as its effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Reaction to fire:		Dangerous Substances:
<b>C</b> ca,S1,d2,a1	Designated standard: EN 50575 : 2014 + A1:2016	NPD
Manufacturer:	Signed for and behalf of the ma	anufacturer by:
ÜNKA KABLO SAN. VE TİC. A.Ş	Barış TABAK / QA & QC Manager	
Saray Mah. Ahmet Tevfik İleri Cad. No : 16/4 Ümraniye / İstanbul / TURKEY	istanbul, 11/08/2021	ÜNKA KABLO SANAX ve TIÇARET A.S. UMRANIYE - ISTANBUL