



Declaration of Performances (DoP)

No. 20170009

Product Type

CY-YSLCY (300/500 V)

² 2 to 34 core - 0,5 mm² ^{*} 2 to 34 core - 1,5 mm²

* 2 to 34 core - 0,75 mm² * 2 to 34 core - 2,5 mm²

* 2 to 34 core - 1,00 mm²

2 to 5 core - 6 mm²

* 2 to 5 core - 10 mm²

* 2 to 7 core - 4 mm² * 2 to 5 core - 16 mm²

* 3 to 5 core - 25 mm²

* 3 to 5 core - 35 mm²

* 3 to 5 core - 50 mm²

* 3 to 4 core - 70 mm²

Batch or Serial Number

M1 4 XXX XXYYYZZZ

Intended use:

Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke

System 3

of assessment and verification of constancy of performance

Notified laboratory body No. NB 1014

The performance of the product identified above is in conformity with the declared performance(s) This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Reaction to fire:		Dangerous Substances:
Eca	Harmonized standard: EN 50575 : 2014 + A1:2016	NPD

Manufacturer: ÜNKA KABLO SAN. VE TİC. A.Ş Saray Mah. Ahmet Tevfik İleri Cad.

No: 16/4 Ümraniye / İstanbul / TURKEY

Signed for and behalf of the manufacturer by: Barış TABAK / QA & QC Manager İstanbul, 17/02/2017

This declaration of performance is issued under the sole responsibility of the manufacturer.