

**Declaration of Performances (DoP)** No. 20170056 Product Type PT1TY2 LSOH OSCR / RE-2X(ST)HSWAH (300/500 V) 1 PR to 20PR - 0,5 mm<sup>2</sup> \* 1 PR to 20PR - 0.75 mm<sup>2</sup> \* 1 PR to 20PR - 1,00 mm<sup>2</sup> \* 1 PR to 20PR - 1,5 mm<sup>2</sup> \* 1 PR to 10PR - 2,5 mm<sup>2</sup> Batch or Serial Number M3 2 XXX XXYYYZZZ Intended use: Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke System 1+ of assessment and verification of constancy of performance Notified laboratory body & Certificate No. NB 2851 The performance of the product identified above is in conformity with the declared performance(s) This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. **Reaction to fire: Dangerous Substances:** Harmonized standard: EN 50575 : 2014 + A1:2016 **C**ca,S1,d2,a1 NPD Signed for and behalf of the manufacturer by: Barış TABAK / QA & QC Manager İstanbul, 11/08/2021

Manufacturer: ÜNKA KABLO SAN. VE TİC. A.Ş Saray Mah. Ahmet Tevfik İleri Cad. No: 16/4 Ümraniye / İstanbul / TURKEY

This declaration of performance is issued under the sole responsibility of the manufacturer.