



## **Declaration of Performances (DoP)**

No. 20170176

**Product Type** 

LIYY-TP (300/500 V)

1 PR to 20PR - 0,5 mm<sup>2</sup>

\* 1 PR to 20PR - 0,75 mm<sup>2</sup>

\* 1 PR to 20PR - 1,00 mm<sup>2</sup>

1 PR to 30PR - 1,5 mm<sup>2</sup>

\* 1 PR to 12PR - 2,5 mm<sup>2</sup>

**Batch or Serial Number** 

M1 4 XXX XXYYYZZZ

Intended use:

Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke

## System 3

of assessment and verification of constancy of performance

## Notified laboratory body No. NB 1014

The performance of the product identified above is in conformity with the declared performance(s) This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Reaction to fire:		Dangerous Substances:
_	Harmonized standard:	
Eca	EN 50575 : 2014 + A1:2016	NPD

Manufacturer: ÜNKA KABLO SAN. VE TİC. A.Ş Saray Mah. Ahmet Tevfik İleri Cad.

No: 16/4 Ümraniye / İstanbul / TURKEY

Signed for and behalf of the manufacturer by: Barış TABAK / QA & QC Manager

İstanbul, 17/02/2017



This declaration of performance is issued under the sole responsibility of the manufacturer.