



ÜNKA KABLO



Declaration of Performances (DoP)

No. 20170003

Product Type

LIYCY (300/500 V)

* 2 to 34 core - 0,5 mm²

* 2 to 34 core - 0,75 mm²

* 2 to 34 core - 1,00 mm²

* 2 to 34 core - 1,5 mm²

* 2 to 34 core - 2,5 mm²

* 2 to 7 core - 4 mm²

* 2 to 5 core - 6 mm²

* 2 to 5 core - 10 mm²

* 2 to 5 core - 16 mm²

* 3 to 5 core - 25 mm²

* 3 to 5 core - 35 mm²

* 3 to 5 core - 50 mm²

* 3 to 4 core - 70 mm²

Batch or Serial Number

M1 4 XXX XYYYZZZ

Intended use:

Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke

System 3

of assessment and verification of constancy of performance

Notified laboratory body No. NB 2184

The performance of the product identified above is in conformity with the declared performance(s) This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Reaction to fire:

Eca

Harmonized standard:

EN 50575 : 2014 + A1:2016

Dangerous Substances:

NPD

Manufacturer:

ÜNKA KABLO SAN. VE TİC. A.Ş
Organize Sanayi Bölgesi Mah. 15
Sk. No: 1/3
Dilovası / Kocaeli / TURKEY

Signed for and behalf of the manufacturer by:

Barış TABAK / QA & QC Manager
İstanbul, 20/02/2026


ÜNKA KABLO
SANAYİ VE TİCARET A.Ş.
ÜMRANIYE - İSTANBUL

This declaration of performance is issued under the sole responsibility of the manufacturer.